

Low Power Prismatic Cell Sizes and Capacities								
Model	Dimensions (mm)			Capacity (mAh)	Impedance (mΩ)	Voltage (v)	Weight (g)	Casing
	Thickness	Width	Height					
053048	5.5	30.0	48.0	650.0	30-70	3.7	20.5	Steel
063048	6.3	30.0	48.0	750.0	30-70	3.7	25.5	Steel
063448	6.5	34.0	48.0	950.0	20-60	3.7	29.0	Steel
073048	7.5	30.0	48.0	900.0	30-70	3.7	28.0	Steel
073448	7.5	34.0	48.0	1000.0	30-70	3.7	32.0	Steel
083448	8.5	34.0	48.0	1050.0	30-70	3.7	35.0	Steel
103447	10.0	34.0	47.0	1400.0	30-70	3.7	40.0	Steel
123582	12.1	35.1	82.0	3000.0	20-60	3.7	90.0	Steel
143447	14.0	34.0	47.0	1800.0	20-60	3.7	56.0	Steel
033450	3.9	34.0	50.0	600.0	40-80	3.7	14.8	Aluminium
043048	4.4	30.0	48.0	600.0	30-80	3.7	14.5	Aluminium
043450	4.4	34.0	50.0	720.0	40-80	3.7	16.5	Aluminium
052246	5.6	22.0	46.0	450.0	40-80	3.7	12.3	Aluminium
052248	5.8	22.0	48.0	500.0	40-80	3.7	13.5	Aluminium
053048	5.4	30.2	48.0	700.0	30-70	3.7	17.5	Aluminium
053048L	5.4	30.2	48.0	680.0	30-70	3.7	17.5	Aluminium
053450	5.4	34.0	50.0	850.0	30-80	3.7	19.5	Aluminium
063048	6.4	30.0	48.0	850.0	30-70	3.7	19.0	Aluminium
063048L	6.4	30.0	48.0	780.0	30-70	3.7	19.0	Aluminium
063448	6.4	34.0	48.0	950.0	30-70	3.7	23.5	Aluminium
063450	6.4	34.0	50.0	950.0	30-70	3.7	23.0	Aluminium
073048	7.5	30.0	48.0	950.0	30-70	3.7	23.1	Aluminium
073448	7.6	34.0	48.0	1100.0	30-70	3.7	27.3	Aluminium
083448	8.5	34.0	48.0	1200.0	30-70	3.7	28.0	Aluminium
103450	10.0	34.0	50.0	1650.0	30-70	3.7	36.2	Aluminium

[Back to Electropaedia](#)